



Minimum Packaging Quantity

Please order by units of minimum packaging quantity.

◆ Metallized polypropylene film capacitors

Series	Voltage (V _{dc})	Rated Capacitance (μF)	Bagged (pcs/box)	Boxed (pcs)	Series	Voltage (V _{dc})	Rated Capacitance (μF)	Bagged (pcs/box)	Boxed (pcs)
TACE	250	15 to 18	-	200	TACC	450	5.6 to 8.2	200	-
		22	-	150			10 to 12	150	-
	400	6.8 to 8.2	-	200			15	100	-
		10 to 12	-	150			18	100	-
	630	0.47 to 3.3	-	200		3.3	200	-	
		4.7	-	150		3.9 to 6.8	150	-	
	1000	0.47 to 1.0	-	200		8.2	100	-	
		1.5	-	150		10	100	-	
TACD	250	0.82 to 1.2	600	-		800	2.2 to 2.7	200	-
		1.5 to 1.8	500	-			3.3 to 3.9	150	-
		2.2	400	-			4.7	100	-
		2.7	300	-			5.6 to 6.8	100	-
		3.3 to 3.9	500	-			1.0	200	-
		4.7	400	-			1.2	150	-
		5.6 to 8.2	300	-			1.5 to 1.8	100	-
		10 to 12	200	-			2.2 to 2.7	100	-
		15	150	-	0.33 to 0.39		800	-	
		315	0.33 to 0.68	800	-		0.47 to 0.68	600	-
	0.82		600	-	0.82 to 1.2	500	-		
	1.0 to 1.8		500	-	1.5 to 1.8	400	-		
	2.2 to 2.7		300	-	2.2 to 2.7	300	-		
	3.3		500	-	3.3	400	-		
	3.9		400	-	3.9 to 6.8	300	-		
	4.7		300	-	8.2	200	-		
	5.6		200	-	10	200	-		
	6.8 to 8.2		200	-	12	150	-		
	10 to 12		150	-	15 to 22	100	-		
	400	0.22 to 0.27	800	-	0.22 to 0.27	800	-		
		0.33 to 0.68	600	-	0.33 to 0.47	600	-		
		0.82 to 1.0	400	-	0.56 to 2.2	400	-		
		1.2 to 1.5	300	-	2.7 to 3.9	300	-		
		1.8 to 2.7	400	-	4.7 to 5.6	200	-		
		3.3 to 3.9	300	-	6.8	200	-		
		4.7	200	-	8.2	150	-		
		5.6 to 6.8	200	-	0.1	700	-		
		8.2	150	-	0.12 to 0.18	600	-		
		500	0.22 to 0.27	800	-	0.22 to 0.33	500	-	
	0.33 to 0.68		500	-	0.39 to 1.2	400	-		
	0.82		300	-	1.5 to 1.8	300	-		
	1.0		400	-	2.2	200	-		
	1.2		500	-	2.7	200	-		
	1.5 to 1.8		400	-	3.3 to 3.9	150	-		
	2.2 to 2.7		300	-	4.7 to 5.6	100	-		
	3.3 to 3.9		200	-	0.056 to 0.082	800	-		
	4.7		150	-	0.1 to 0.12	600	-		
	630		0.1 to 0.15	800	-	0.15	500	-	
		0.18	600	-	0.18 to 0.27	400	-		
		0.22 to 0.33	500	-	0.33 to 0.47	300	-		
		0.39	400	-	0.56 to 0.68	400	-		
		0.47	300	-	0.82 to 1.0	300	-		
		0.56 to 1.0	400	-	1.2 to 1.8	200	-		
		1.2 to 1.5	300	-	2.2	150	-		
		1.8	200	-	2.7 to 3.9	100	-		
		2.2 to 2.7	200	-	0.033 to 0.039	800	-		
		3.3	150	-	0.047 to 0.082	600	-		
	800	3.9 to 5.6	100	-	0.082 to 0.15	400	-		
		0.056 to 0.082	800	-	0.18 to 0.22	300	-		
		0.1 to 0.12	600	-	0.27 to 0.33	400	-		
		0.15 to 0.27	500	-	0.39 to 0.56	300	-		
		0.33 to 0.68	400	-	0.68 to 1.0	200	-		
		0.82 to 1.0	300	-	1.2	150	-		
		1.2 to 1.8	200	-	TACB	400	800	200	-
		2.2	150	-					
		2.7 to 3.9	100	-					
		0.033 to 0.039	800	-					
	0.047 to 0.082	600	-						
	0.1 to 0.12	500	-						
	0.15 to 0.18	400	-						
	0.22 to 0.27	300	-						
	0.33 to 0.39	400	-						
	0.47 to 0.68	300	-						
	0.82 to 1.0	200	-						
	1.2	150	-						

Product specifications in this catalog are subject to change without notice. Request our product specifications before purchase and/or use. Please use our products based on the information contained in this catalog and product specifications.



Series	Voltage (V _{dc})	Rated Capacitance (μF)	Bagged (pcs/box)	Boxed (pcs)	Series	Voltage (V _{dc})	Rated Capacitance (μF)	Bagged (pcs/box)	Boxed (pcs)
HACE	630	0.47 to 1.0	-	200	HACB	630	0.033 to 0.039	800	-
		1.5	-	150			0.047 to 0.068	600	-
	1250	0.47 to 0.68	-	150			0.082	500	-
		1.0 to 1.5	-	100			0.10 to 0.18	400	-
		1600	0.27 to 0.33	-			150	0.22 to 0.27	300
2000	0.18 to 0.22	-	150	0.33 to 0.39			400	-	
HACD	630	0.047 to 0.082	600	-			0.47 to 0.56	300	-
		0.1	500	-			0.68 to 0.82	200	-
		0.12 to 0.22	400	-			0.1 to 0.12	150	-
		0.27	300	-			0.018	800	-
		0.33	500	-		0.022 to 0.033	600	-	
		0.39 to 0.68	400	-		0.039 to 0.056	500	-	
		0.82	300	-		0.068 to 0.1	400	-	
		1.0 to 1.2	200	-		0.12	300	-	
		1.5	200	-		0.15	500	-	
		1000	0.033 to 0.056	600		-	0.18 to 0.27	400	-
	0.068		500	-		0.33	300	-	
	0.082 to 0.1		400	-		0.39 to 0.56	200	-	
	0.12 to 0.47		300	-		0.68	150	-	
	0.56 to 0.82		200	-		0.82 to 1.2	100	-	
	1.0		200	-	0.012 to 0.027	600	-		
	1.2		150	-	0.033	500	-		
	1250		0.018 to 0.039	600	-	0.039 to 0.056	400	-	
		0.047 to 0.082	400	-	0.068 to 0.082	300	-		
		0.1 to 0.12	300	-	0.1 to 0.12	400	-		
		0.15 to 0.18	400	-	0.15 to 0.18	300	-		
		0.22 to 0.27	300	-	0.22 to 0.33	200	-		
		0.33 to 0.47	200	-	0.39 to 0.56	150	-		
		0.56 to 0.68	150	-	0.68 to 0.82	100	-		
		0.82 to 1.2	100	-	1.0	100	-		
	1600	0.0068 to 0.012	600	-	0.0047 to 0.0068	600	-		
		0.015	500	-	0.0082 to 0.012	500	-		
		0.018 to 0.027	400	-	0.015	400	-		
		0.033 to 0.068	300	-	0.018 to 0.033	300	-		
		0.082 to 0.15	400	-	0.039	500	-		
		0.18 to 0.22	200	-	0.047 to 0.082	400	-		
		0.27	200	-	0.1 to 0.12	300	-		
		0.33	150	-	0.15 to 0.18	200	-		
		2000	0.0033 to 0.0056	600	-	0.22 to 0.27	150	-	
			0.0068	500	-	0.33 to 0.47	100	-	
	0.008 to 0.015		400	-	0.001 to 0.0039	800	-		
	0.018 to 0.022		300	-	0.0047 to 0.0056	600	-		
	0.027 to 0.068		400	-	0.0068	500	-		
	0.082		300	-	0.0082 to 0.012	400	-		
	0.1 to 0.15		200	-	0.015 to 0.022	300	-		
	0.18		150	-	0.027 to 0.047	400	-		
2500	0.220 to 0.330	100	-	0.056	300	-			
	0.015 to 0.022	300	-	0.068 to 0.082	200	-			
	0.027 to 0.033	200	-	0.1	200	-			
	0.039 to 0.056	300	-	0.12 to 0.15	150	-			
3150	0.068 to 0.082	200	-	0.18 to 0.27	100	-			
	0.1	150	-	0.0047 to 0.0068	200	-			
	0.0068 to 0.01	300	-	0.0082	400	-			
	0.012 to 0.015	200	-	0.010 to 0.012	300	-			
	0.018 to 0.027	300	-	0.015	200	-			
4000	0.033 to 0.039	200	-	0.018	200	-			
	0.039 to 0.056	300	-	0.022 to 0.033	150	-			
	0.068 to 0.082	200	-	0.0027	300	-			
	0.1	150	-	0.0033 to 0.0047	200	-			
	0.012 to 0.015	300	-	0.0056 to 0.0068	300	-			
4000	0.018	200	-	0.0082 to 0.01	200	-			
	0.022 to 0.027	150	-	0.012 to 0.018	150	-			