

DLCAP™ Module



For an easy usage of Electric Double Layer Capacitor DLCAP™, we have prepared modules. By connecting multiple modules, modules with higher voltage and larger capacitance can be made.

● Application Examples

◆ Energy Saving

- Peak power assistance
- Effective recapture of kinetic energy

◆ Renewable Energy

- Stabilization of windmill power
- High efficient charge of solar energy
- Electricity assist for fuel cell

◆ Safety & Emergency Applications

- Momentary large power supply at power failure
- Back up for power source failure



● DLCAP™ Module

◆ FEATURES

- Built-in voltage balance circuit.
- Built-in failure detection circuit.
- Built-in thermistor for temperature monitor.

◆ SPECIFICATIONS

Items	Specifications	
Operating Temperature	-40°C ~ +70°C	
Capacitance Tolerance	+10%/-15% (20°C)	
Temperature Characteristics	Capacitance Change	≤ ±30% of the measured value at 20°C
	Internal Resistance Change	≤ 1200% of the internal resistance maximum value given in the ratings tables (-30°C)
Load Life Test	After the capacitors are subjected to the rated DC voltage at 70°C for 2000 hours, the following specifications shall be satisfied when they are restored to 20°C .	
	Capacitance Change	≤ ±30% of the initial measured value at 20°C
	Internal Resistance Change	≤ 300% of the internal resistance maximum value given in the ratings tables
Bias Humidity Test	After the capacitors are left at 40°C and 90 to 95%RH for 500 hours without voltage applied, the following specifications shall be satisfied when they are restored to 20°C .	
	Capacitance Change	≤ ±30% of the initial measured value at 20°C
	Internal Resistance Change	≤ 300% of the internal resistance maximum value given in the ratings tables
Insulation Resistance	The measured value between the lumped terminal and the case using 500Vdc insulation resistance meter shall be more than 100MΩ.	
Insulation Withstand Voltage	No abnormality after the AC 2500V is applied between lumped terminal and package for 1 minute. package for 1 minute.	

◆ STANDARD RATINGS

Rated Voltage [V]	Capacitance		Case Size			Internal Resistance		Weight* ¹ [kg]	Energy Storage* ² [Wh]	Part No.
	Typ. (rated) [F]	Min[F]	D [mm]	W [mm]	H [mm]	Typ. [mΩ]	Max. [mΩ]			
7.5	133	113	54	180	97	6.6	7.8	0.7	1.0	MDXE7R5S131SB3111A
	266	226			137	3.6	4.2	1.0	2.1	MDXE7R5S261SB3111A
	400	340			182	2.7	3.3	1.2	3.1	MDXE7R5S401PB3111A
	466	396			182	3.6	4.2	1.2	3.6	MDXE7R5S461PB3111A

* 1 Reference data

Connecting parts are attached.

* 2 The energy storage capacity (Wh) described in this product is calculated based on "Guidebook on Transportation of Electric Double Layer Capacitors for Electrical and Electronic Equipment (JEITA)".

● DLCAP™ Custom Module Acceptable

Custom designs are available on requests.


◆ Custom design examples;

- High voltage application
- Large capacitance application
- High current application
- Proper balance circuit suggestion
- Usage under vibration or physical shocks
- Optional circuits for charge/discharge control

Please consult us if custom specification is required.

- If you need to connect more than 8 items in series please consult us.

◆ DIMENSIONS



◆ Screw Specification

Screw : M6

Tightening torque : 5.2Nm±10%