

## Minimum Packaging Quantity

Please order by units of minimum packaging quantity.

### ◆ Metallized polypropylene film capacitors

Series	Rated voltage range (V)	Rated capacitance range (μF)	Outer box		
			Q'ty (pcs)	No. of stacks	Q'ty (pcs)
TACE	250	15 to 18	50/stack	4	200
		22	50/stack	3	150
	400	6.8 to 8.2	50/stack	4	200
		10 to 12	50/stack	3	150
	630	0.47 to 3.3	50/stack	4	200
		4.7	50/stack	3	150
	1000	0.47 to 1.0	50/stack	4	200
		1.5	50/stack	3	150

  

Series	Rated voltage range (V)	Rated capacitance range (μF)	Outer box		
			Q'ty (pcs)	No. of bags	Q'ty (pcs)
TACD	250	0.82 to 1.2	100	6	600
		1.5 to 1.8	100	5	500
		2.2	100	4	400
		2.7	100	3	300
		3.3 to 3.9	100	5	500
		4.7	100	4	400
		5.6 to 8.2	100	3	300
		10 to 12	50	4	200
		15	50	3	150
		315	0.33 to 0.68	100	8
	0.82		100	6	600
	1.0 to 1.8		100	5	500
	2.2 to 2.7		100	3	300
	3.3		100	5	500
	3.9		100	4	400
	4.7		100	3	300
	5.6		100	2	200
	6.8 to 8.2		50	4	200
	10 to 12		50	3	150
	400	0.22 to 0.27	100	8	800
		0.33 to 0.68	100	6	600
		0.82 to 1.0	100	4	400
		1.2 to 1.5	100	3	300
		1.8 to 2.7	100	4	400
		3.3 to 3.9	100	3	300
		4.7	100	2	200
		5.6 to 6.8	50	4	200
		8.2	50	3	150
		500	0.22 to 0.27	100	8
	0.33 to 0.68		100	5	500
	0.82		100	3	300
	1.0		100	4	400
	1.2		100	5	500
	1.5 to 1.8		100	4	400
	2.2 to 2.7		100	3	300
	3.3 to 3.9		50	4	200
	4.7		50	3	150
	630		0.1 to 0.15	100	8
		0.18	100	6	600
		0.22 to 0.33	100	5	500
		0.39	100	4	400
		0.47	100	3	300
		0.56 to 1.0	100	4	400
		1.2 to 1.5	100	3	300
		1.8	100	2	200
		2.2 to 2.7	50	4	200
		3.3	50	3	150
	800	3.9 to 5.6	50	2	100
		0.056 to 0.082	100	8	800
		0.1 to 0.12	100	6	600
		0.15 to 0.27	100	5	500
		0.33 to 0.68	100	4	400
		0.82 to 1.0	100	3	300
		1.2 to 1.8	50	4	200
		2.2	50	3	150
		2.7 to 3.9	50	2	100
		1000	0.033 to 0.039	100	8
	0.047 to 0.082		100	6	600
	0.1 to 0.12		100	5	500
	0.15 to 0.18		100	4	400

  

Series	Rated voltage range (V)	Rated capacitance range (μF)	Outer box		
			Q'ty (pcs)	No. of bags	Q'ty (pcs)
TACD	1000	0.22 to 0.27	100	3	300
		0.33 to 0.39	100	4	400
		0.47 to 0.68	100	3	300
		0.82 to 1.0	50	4	200
		1.2	50	3	150
	450	5.6 to 8.2	50	4	200
		10 to 12	50	3	150
		15	50	2	100
		18	25	4	100
		3.3	50	4	200
TACC	630	3.9 to 6.8	50	3	150
		8.2	50	2	100
		10	25	4	100
		2.2 to 2.7	50	4	200
		3.3 to 3.9	50	3	150
	800	4.7	50	2	100
		5.6 to 6.8	25	4	100
		1.0	50	4	200
		1.2	50	3	150
		1.5 to 1.8	50	2	100
TACB	250	0.33 to 0.39	100	8	800
		0.47 to 0.68	100	6	600
		0.82 to 1.2	100	5	500
		1.5 to 1.8	100	4	400
		2.2 to 2.7	100	3	300
	315	3.3	100	4	400
		3.9 to 6.8	100	3	300
		8.2	100	2	200
		10	50	4	200
		12	50	3	150
15 to 22		50	2	100	
0.22 to 0.27		100	8	800	
0.33 to 0.47		100	6	600	
0.56 to 2.2		100	4	400	
2.7 to 3.9		100	3	300	
400	4.7 to 5.6	100	2	200	
	6.8	50	4	200	
	8.2	50	3	150	
	0.1	100	7	700	
	0.12 to 0.18	100	6	600	
	0.22 to 0.33	100	5	500	
	0.39 to 1.2	100	4	400	
	1.5 to 1.8	100	3	300	
	2.2	100	2	200	
	2.7	50	4	200	
630	3.3 to 3.9	50	3	150	
	4.7 to 5.6	50	2	100	
	0.056 to 0.082	100	8	800	
	0.1 to 0.12	100	6	600	
	0.15	100	5	500	
	0.18 to 0.27	100	4	400	
	0.33 to 0.47	100	3	300	
	0.56 to 0.68	100	4	400	
	0.82 to 1.0	100	3	300	
	1.2 to 1.8	50	4	200	
800	2.2	50	3	150	
	2.7 to 3.9	50	2	100	
	0.033 to 0.039	100	8	800	
	0.047 to 0.068	100	6	600	
	0.082 to 0.15	100	4	400	
	0.18 to 0.22	100	3	300	
	0.27 to 0.33	100	4	400	
	0.39 to 0.56	100	3	300	
	0.68 to 1.0	50	4	200	
	1.2	50	3	150	

Series	Rated voltage range (V)	Rated capacitance range (μF)	Outer box		
			Q'ty (pcs)	No. of stacks	Q'ty (pcs)
HACE	630	0.47 to 1.0	50/stack	4	200
		1.5	50/stack	3	150
	1250	0.47 to 0.68	50/stack	3	150
		1.0 to 1.5	50/stack	2	100
	1600	0.27 to 0.33	50/stack	3	150
2000	0.18 to 0.22	50/stack	3	150	

  

Series	Rated voltage range (V)	Rated capacitance range (μF)	Inner bag	Outer box	
			Q'ty (pcs)	No. of bags	Q'ty (pcs)
HACD	630	0.047 to 0.082	100	6	600
		0.1	100	5	500
		0.12 to 0.22	100	4	400
		0.27	100	3	300
		0.33	100	5	500
		0.39 to 0.68	100	4	400
		0.82	100	3	300
		1.0 to 1.2	100	2	200
		1.5	50	4	200
	1000	0.033 to 0.056	100	6	600
		0.068	100	5	500
		0.082 to 0.1	100	4	400
		0.12 to 0.47	100	3	300
		0.56 to 0.82	100	2	200
		1.0	50	4	200
	1250	0.018 to 0.039	100	6	600
		0.047 to 0.082	100	4	400
		0.1 to 0.12	100	3	300
		0.15 to 0.18	100	4	400
		0.22 to 0.27	100	3	300
		0.33 to 0.47	100	2	200
	1600	0.56 to 0.68	50	3	150
		0.82 to 1.2	50	2	100
		0.0068 to 0.012	100	6	600
		0.015	100	5	500
		0.018 to 0.027	100	4	400
		0.033 to 0.068	100	3	300
	2000	0.082 to 0.15	100	4	400
		0.18 to 0.22	100	2	200
		0.27	50	4	200
		0.33	50	3	150
		0.0033 to 0.0056	100	6	600
		0.0068	100	5	500
		0.008 to 0.015	100	4	400
		0.018 to 0.022	100	3	300
		0.027 to 0.068	100	4	400
		0.082	100	3	300
		0.1 to 0.15	100	2	200
		0.18	50	3	150
	2500	0.220 to 0.330	50	2	100
		0.015 to 0.022	100	3	300
		0.027 to 0.033	100	2	200
		0.039 to 0.056	100	3	300
		0.068 to 0.082	100	2	200
	3150	0.1	50	3	150
0.0068 to 0.01		100	3	300	
0.012 to 0.015		100	2	200	
0.018 to 0.027		100	3	300	
0.033 to 0.039		50	4	200	
4000	0.047	50	3	150	
	0.0039 to 0.0056	100	3	300	
	0.0068 to 0.01	100	2	200	
	0.012 to 0.015	100	3	300	
	0.018	50	4	200	
0.022 to 0.027	50	3	150		

  

Series	Rated voltage range (V)	Rated capacitance range (μF)	Inner bag	Outer box	
			Q'ty (pcs)	No. of bags	Q'ty (pcs)
HACB	630	0.033 to 0.039	100	8	800
		0.047 to 0.068	100	6	600
		0.082	100	5	500
		0.10 to 0.18	100	4	400
		0.22 to 0.27	100	3	300
		0.33 to 0.39	100	4	400
		0.47 to 0.56	100	3	300
		0.68 to 0.82	100	2	200
		0.1 to 0.12	50	3	150
		0.018	100	8	800
	1000	0.022 to 0.033	100	6	600
		0.039 to 0.056	100	5	500
		0.068 to 0.1	100	4	400
		0.12	100	3	300
		0.15	100	5	500
		0.18 to 0.27	100	4	400
		0.33	100	3	300
		0.39 to 0.56	100	2	200
		0.68	50	3	150
		0.82 to 1.2	50	2	100
	1250	0.012 to 0.027	100	6	600
		0.033	100	5	500
		0.039 to 0.056	100	4	400
		0.068 to 0.082	100	3	300
		0.1 to 0.12	100	4	400
		0.15 to 0.18	100	3	300
		0.22 to 0.33	50	4	200
		0.39 to 0.56	50	3	150
		0.68 to 0.82	50	2	100
		1.0	25	4	100
	1600	0.0047 to 0.0068	100	6	600
		0.0082 to 0.012	100	5	500
		0.015	100	4	400
		0.018 to 0.033	100	3	300
		0.039	100	5	500
		0.047 to 0.082	100	4	400
		0.1 to 0.12	100	3	300
		0.15 to 0.18	100	2	200
		0.22 to 0.27	50	3	150
		0.33 to 0.47	50	2	100
	2000	0.001 to 0.0039	100	8	800
		0.0047 to 0.0056	100	6	600
		0.0068	100	5	500
		0.0082 to 0.012	100	4	400
		0.015 to 0.022	100	3	300
0.027 to 0.047		100	4	400	
0.056		100	3	300	
0.068 to 0.082		100	2	200	
0.1		50	4	200	
0.12 to 0.15		50	3	150	
3150	0.18 to 0.27	50	2	100	
	0.0047 to 0.0068	100	2	200	
	0.0082	100	4	400	
	0.010 to 0.012	100	3	300	
	0.015	100	2	200	
4000	0.018	50	4	200	
	0.022 to 0.033	50	3	150	
	0.0027	100	3	300	
	0.0033 to 0.0047	100	2	200	
	0.0056 to 0.0068	100	3	300	
0.0082 to 0.01	50	4	200		
0.012 to 0.018	50	3	150		