

List of errata : 2011/2012 Aluminum Electrolytic Capacitor (CAT. NO. E1001L)

November 1, 2011

Page of printed catalog	Item/Series	Subjects	Error	Correct																															
2	Series Table	KYA series	Solvent resistant: ●	KYA is NOT Solvent resistant product																															
23	Conductive polymer Product list	Case size of 4V270uF, PXE series	6.3x 6.8	6.3x 5.8																															
		ESR of 4V680uF, PXF series	19	9																															
		Case size of 6.3V150uF, PXA series	6x6.7	8x6.7																															
		ESR of 6.3V470uF, PXF series	19	9																															
		Case size of 6.3V820uF, PXE series	8x 10.2 8x 12.2	8x 10 8x 12																															
25	Conductive polymer Product list	Series name of 16V270uF(8 × 8) Ripple current of 25V68uF, PS series	PSE 3820	PSF 3320																															
27	Conductive polymer type PKX	Part No. on the "STANDARD RATINGS"	E r r o r	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Size code</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td rowspan="2">2.5</td> <td>330</td> <td>F46</td> <td>APXK2R5ARA331ME46G</td> </tr> <tr> <td>560</td> <td>F61</td> <td>APXK2R5ARA561MF61G</td> </tr> <tr> <td rowspan="2">4</td> <td>180</td> <td>F46</td> <td>APXK4R0ARA181ME46G</td> </tr> <tr> <td>390</td> <td>F61</td> <td>APXK4R0ARA391ME61G</td> </tr> <tr> <td rowspan="4">6.3</td> <td>150</td> <td>F46</td> <td>APXK6R3ARA151MF46G</td> </tr> <tr> <td>220</td> <td>F46</td> <td>APXK6R3ARA221ME46G</td> </tr> <tr> <td>330</td> <td>F61</td> <td>APXK6R3ARA331ME61G</td> </tr> <tr> <td>100</td> <td>F61</td> <td>APXK160ARA101MF61G</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Size code	Part No.	2.5	330	F46	APXK2R5ARA331M E 46G	560	F61	APXK2R5ARA561M F 61G	4	180	F46	APXK4R0ARA181M E 46G	390	F61	APXK4R0ARA391M E 61G	6.3	150	F46	APXK6R3ARA151M F 46G	220	F46	APXK6R3ARA221M E 46G	330	F61	APXK6R3ARA331M E 61G	100	F61	APXK160ARA101M F 61G
			WV (Vdc)	Cap (μF)	Size code	Part No.																													
2.5	330	F46	APXK2R5ARA331M E 46G																																
	560	F61	APXK2R5ARA561M F 61G																																
4	180	F46	APXK4R0ARA181M E 46G																																
	390	F61	APXK4R0ARA391M E 61G																																
6.3	150	F46	APXK6R3ARA151M F 46G																																
	220	F46	APXK6R3ARA221M E 46G																																
	330	F61	APXK6R3ARA331M E 61G																																
	100	F61	APXK160ARA101M F 61G																																
C o r r e c t	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Size code</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td rowspan="2">2.5</td> <td>330</td> <td>F46</td> <td>APXK2R5ARA331MF46G</td> </tr> <tr> <td>560</td> <td>F61</td> <td>APXK2R5ARA561MF61G</td> </tr> <tr> <td rowspan="2">4</td> <td>180</td> <td>F46</td> <td>APXK4R0ARA181MF46G</td> </tr> <tr> <td>390</td> <td>F61</td> <td>APXK4R0ARA391MF61G</td> </tr> <tr> <td rowspan="4">6.3</td> <td>150</td> <td>F46</td> <td>APXK6R3ARA151MF46G</td> </tr> <tr> <td>220</td> <td>F46</td> <td>APXK6R3ARA221MF46G</td> </tr> <tr> <td>330</td> <td>F61</td> <td>APXK6R3ARA331MF61G</td> </tr> <tr> <td>100</td> <td>F61</td> <td>APXK160ARA101MF61G</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Size code	Part No.	2.5	330	F46	APXK2R5ARA331M F 46G	560	F61	APXK2R5ARA561M F 61G	4	180	F46	APXK4R0ARA181M F 46G	390	F61	APXK4R0ARA391M F 61G	6.3	150	F46	APXK6R3ARA151M F 46G	220	F46	APXK6R3ARA221M F 46G	330	F61	APXK6R3ARA331M F 61G	100	F61	APXK160ARA101M F 61G			
WV (Vdc)	Cap (μF)	Size code	Part No.																																
2.5	330	F46	APXK2R5ARA331M F 46G																																
	560	F61	APXK2R5ARA561M F 61G																																
4	180	F46	APXK4R0ARA181M F 46G																																
	390	F61	APXK4R0ARA391M F 61G																																
6.3	150	F46	APXK6R3ARA151M F 46G																																
	220	F46	APXK6R3ARA221M F 46G																																
	330	F61	APXK6R3ARA331M F 61G																																
	100	F61	APXK160ARA101M F 61G																																
29	Conductive polymer type PXS	Size code on the "STANDARD RATINGS"	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Size code</th> </tr> </thead> <tbody> <tr> <td>6.3</td> <td>120</td> <td>E61</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Size code	6.3	120	E 61	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Size code</th> </tr> </thead> <tbody> <tr> <td>6.3</td> <td>120</td> <td>F61</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Size code	6.3	120	F 61																			
WV (Vdc)	Cap (μF)	Size code																																	
6.3	120	E 61																																	
WV (Vdc)	Cap (μF)	Size code																																	
6.3	120	F 61																																	
38	Conductive polymer type PSG	Capacitance Tolerance on the "SPECIFICATIONS" Surge Voltage on the "SPECIFICATIONS"	P 20% (M) Rated voltage(V) B 1.15	± 20% (M) Rated voltage(V) X 1.15																															
86	Chip type MKB	Part No. on the "STANDARD RATINGS"	E r r o r	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Size code</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td rowspan="2">400</td> <td>3.9</td> <td>JA0</td> <td>EMKB401ADA3R3MJA0G</td> </tr> <tr> <td>4.7</td> <td>JA0</td> <td>EMKB401ADA3R3MJA0G</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Size code	Part No.	400	3.9	JA0	EMKB401ADA 3R 3MJA0G	4.7	JA0	EMKB401ADA 3R 3MJA0G																				
			WV (Vdc)	Cap (μF)	Size code	Part No.																													
400	3.9	JA0	EMKB401ADA 3R 3MJA0G																																
	4.7	JA0	EMKB401ADA 3R 3MJA0G																																
C o r r e c t	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Size code</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td rowspan="2">400</td> <td>3.9</td> <td>JA0</td> <td>EMKB401ADA3R9MJA0G</td> </tr> <tr> <td>4.7</td> <td>JA0</td> <td>EMKB401ADA4R7MJA0G</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Size code	Part No.	400	3.9	JA0	EMKB401ADA 3R 9MJA0G	4.7	JA0	EMKB401ADA 4R 7MJA0G																							
WV (Vdc)	Cap (μF)	Size code	Part No.																																
400	3.9	JA0	EMKB401ADA 3R 9MJA0G																																
	4.7	JA0	EMKB401ADA 4R 7MJA0G																																
103	Radial lead type SMQ	Dissipation Factor(tan δ) on the "SPECIFICATIONS"	When nominal capacitance exceeds 1,000 μF, add 0.02 to the value above for each 1,000 M F increase.	When nominal capacitance exceeds 1,000 μF, add 0.02 to the value above for each 1,000 μ F increase.																															
109	Radial lead type SMG	Dissipation Factor(tan δ) on the "SPECIFICATIONS"	When nominal capacitance exceeds 1,000 μF, add 0.02 to the value above for each 1,000 M F increase.	When nominal capacitance exceeds 1,000 μF, add 0.02 to the value above for each 1,000 μ F increase.																															
140	Radial lead type LXV	Part No. on the "STANDARD RATINGS"	E r r o r	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Case size φD × L(mm)</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td rowspan="2">6.3</td> <td rowspan="2">10,000</td> <td rowspan="2">18 × 30</td> <td>ELXV6R3E□□103MM30SE</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Case size φD × L(mm)	Part No.	6.3	10,000	18 × 30	ELXV6R3E□□103MM 30 SE																							
			WV (Vdc)	Cap (μF)	Case size φD × L(mm)	Part No.																													
6.3	10,000	18 × 30	ELXV6R3E□□103MM 30 SE																																
			C o r r e c t	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Case size</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td>6.3</td> <td>10,000</td> <td>18 × 30</td> <td>ELXV6R3E□□103MM30S</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Case size	Part No.	6.3	10,000	18 × 30	ELXV6R3E□□103MM 30 S																							
WV (Vdc)	Cap (μF)	Case size	Part No.																																
6.3	10,000	18 × 30	ELXV6R3E□□103MM 30 S																																
141	Radial lead type LXV	Case size on the "STANDARD RATINGS"	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Case size φD × L (mm)</th> </tr> </thead> <tbody> <tr> <td>80</td> <td>27</td> <td>6.8 × 15</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Case size φD × L (mm)	80	27	6.8 × 15	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Case size φD × L (mm)</th> </tr> </thead> <tbody> <tr> <td>80</td> <td>27</td> <td>6.3 × 15</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Case size φD × L (mm)	80	27	6.3 × 15																			
WV (Vdc)	Cap (μF)	Case size φD × L (mm)																																	
80	27	6.8 × 15																																	
WV (Vdc)	Cap (μF)	Case size φD × L (mm)																																	
80	27	6.3 × 15																																	
180	Snap-in type SMM	Case size on the "STANDARD RATINGS"	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Case size φD × L (mm)</th> </tr> </thead> <tbody> <tr> <td>160</td> <td>1800</td> <td>35 × 30</td> </tr> <tr> <td>200</td> <td>560</td> <td>30 × 20</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Case size φD × L (mm)	160	1800	35 × 30	200	560	30 × 20	<table border="1"> <thead> <tr> <th>WV (Vdc)</th> <th>Cap (μF)</th> <th>Case size φD × L (mm)</th> </tr> </thead> <tbody> <tr> <td>160</td> <td>1800</td> <td>35 × 35</td> </tr> <tr> <td>200</td> <td>560</td> <td>30 × 25</td> </tr> </tbody> </table>	WV (Vdc)	Cap (μF)	Case size φD × L (mm)	160	1800	35 × 35	200	560	30 × 25													
WV (Vdc)	Cap (μF)	Case size φD × L (mm)																																	
160	1800	35 × 30																																	
200	560	30 × 20																																	
WV (Vdc)	Cap (μF)	Case size φD × L (mm)																																	
160	1800	35 × 35																																	
200	560	30 × 25																																	
199	Snap-in type LXM	D.F.(tan δ) of Endurance	≤ 200% of the initial specified value	≤ 250% of the initial specified value																															
245	Screw-mount type LXR	Mounting Clamp Code :B of "DIMENSIONS"	E r r o r	<table border="1"> <thead> <tr> <th></th> <th>A</th> <th>φDB</th> <th>W</th> <th>F</th> </tr> </thead> <tbody> <tr> <td>63.5</td> <td>90</td> <td>76</td> <td>80</td> <td>28.0</td> </tr> <tr> <td>76.2</td> <td>104.5</td> <td>90</td> <td>93.5</td> <td>31.5</td> </tr> </tbody> </table>		A	φDB	W	F	63.5	90	76	80	28.0	76.2	104.5	90	93.5	31.5																
				A	φDB	W	F																												
63.5	90	76	80	28.0																															
76.2	104.5	90	93.5	31.5																															
C o r r e c t	<table border="1"> <thead> <tr> <th>φD</th> <th>A</th> <th>B</th> <th>W</th> <th>F</th> </tr> </thead> <tbody> <tr> <td>63.5</td> <td>90</td> <td>76</td> <td>80</td> <td>28.0</td> </tr> <tr> <td>76.2</td> <td>104.5</td> <td>90</td> <td>93.5</td> <td>31.5</td> </tr> </tbody> </table>	φD	A	B	W	F	63.5	90	76	80	28.0	76.2	104.5	90	93.5	31.5																			
φD	A	B	W	F																															
63.5	90	76	80	28.0																															
76.2	104.5	90	93.5	31.5																															