

**◆Packaging**

		B o x			
Configuration					
Dimensions (mm)		TFA, TBA (T15, T25)	TEA, TFA, TAA, TBA (T1, T15, T2, T25)		TFB, TBB, TLB (T8, T7, T71)
		5V, 7V, 9V, 9H	10V, 12V, 14V, 12H, 15H	10SE, 12SE, 14SE	10V, 12V, 10SE, 12SE, 14SE, 10SV, 12SV, 14SV
	W	325±5	330±5	340 max.	340 max.
	H	47±3	57±3	65 max.	65 max.
	B	280±10	315±10	360 max.	360 max.

**◆Packaging Quantity**

Type	Taping Code	150K~271K	331K~621K
5V,7V,9V,9H	TFA, TBA(T15, T25)	1500	1000
10V,12V,14V	TEA, TFA, TAA, TBA (T1, T15, T2, T25)	800	500
10SE,12SE,14SE		600	500
12H,15H		800	
10V,12V,14V	TFB, TBB (T8, T7)	1000	1000
10SE		1000	800
12SE,14SE		500	400
10SV,12SV	TLB (T71)	500	500
14SV		300	300

NOTE : The code (T1, T15, T2, T25, T8, T7) are the old taping code

**◆Others**

- 1) On the box or the reel, the following are noted.
  1. Part number
  2. Lot number
  3. Quantity
  4. Country of origin
- 2) Minimum order quantity shall be the packaging quantity per one box one reel.

**MINIMUM ORDER QUANTITY**

Please order by units of minimum order quantity.

**◆Disk Type**

Series	Type	Varistor Voltage Range (V)	Straight Lead Quantity (pcs)	Formed/Cut Lead Quantity (pcs)
V	5V, 7V, 9V	All Voltage Range	100	100
	10V, 12V	All Voltage Range	100	100
	14V	15~1200	100	100
		1500~1800	50	50
	20V	18~1100	50	50
1200~1800		25	25	
SE	20SE	All Voltage Range	50	50
H	9H, 12H, 15H	All Voltage Range	100	100
	23H	All Voltage Range	50	50
GF	15GF	All Voltage Range	50	—
	23GF	All Voltage Range	25	—
32HP	—	All Voltage Range	5	—

**◆Axial Lead Type**

Series	Type	Varistor Voltage Range (V)	Straight Lead Quantity (pcs)	Formed/Cut Lead Quantity (pcs)
A	4A	All Voltage Range	100	—
	10A	All Voltage Range	50	—