

☆: Recommendation products
 (AEC-Q200): AEC-Q200 compliant. Please contact your local Chemi-Con office for more details, test data, information and also non indicated products.

CONDUCTIVE POLYMER ALUMINUM SOLID CAPACITORS

RESIN-MOLDED SURFACE MOUNT TYPE

3D Click here!




Resin-Molded Type Digitalization Super Low ESR

PMA
105°C 5,000H

SURFACE MOUNT TYPE

3D Click here!




Surface Mount Type Digitalization Super Low ESR

125°C High Temperature

- PXA** 105°C 3,000/15,000H
- *PXF** Low ESR
- PXS** Long Life
- PXH** 125°C 1,000H
- PXD** 125°C 2,000H
- PXE** 105°C 15,000H
- *PXK** Downsizing
- *PXG** 105°C 16 to 25V
- PXJ** Downsizing
- PXN** High moisture resistance (New!)
- PXT** High moisture resistance

RADIAL LEAD TYPE

3D Click here!




Radial Lead Type Digitalization Super Low ESR

- *PSF** Low ESR, Long Life
- PSJ** Low ESR
- PSC** 105°C 15,000H
- PSE** Long Life
- *PSG** 105°C 16 to 35V
- *PSK** Downsizing, Long Life

CONDUCTIVE POLYMER HYBRID ALUMINUM ELECTROLYTIC CAPACITORS

SURFACE MOUNT TYPE

3D Click here!




Surface Mount Type Digitalization Super Low ESR Automotive Application

125°C/135°C High Temperature

- HXB** 105°C 5,000H
- HXD** 105°C 5,000H
- HXA** 125°C 4,000H
- HXC** 125°C 4,000H
- HXE** 135°C 2,000/4,000H (New!)

RADIAL LEAD TYPE

3D Click here!



Radial Lead Type Digitalization Super Low ESR Automotive Application


125°C/135°C High Temperature

- HSD** 105°C 5,000H
- HSC** 125°C 4,000H
- HSE** 135°C 4,000H (New!)

ALUMINUM ELECTROLYTIC CAPACITORS

SURFACE MOUNT TYPE (CE32)

3D Click here!



Surface Mount Type (CE32) Digitalization

105°C High Voltage

- MKB** 400V

105°C Low Impedance

- MVY** 105°C 1,000 to 5,000H
- *MZA** 105°C 2,000/5,000H Low Z
- MZJ** 105°C 2,000H Low Z
- MZR** 105°C 2,000H Downsizing
- MZS** 105°C 2,000H higher capacitance (New!)

Surface Mount Standard

- *MVA** 85°C
- *MVE** 105°C

105°C Low Impedance / Long Life

- MLA** 105°C 3,000H Long Life
- MZE** 105°C 7,000/8,000H Long Life
- MZF** 105°C 10,000H Long Life
- MZK** 105°C 5,000H Low Profile

125°C High Temperature

- MVH** 125°C
- MHL** 125°C 2,000/4,000H Downsizing
- MHS** 125°C 5,000H Upgrade!
- *MHB** 125°C Low ESR
- MHJ** 125°C Low ESR Low ESR
- MHK** 125°C Low ESR Upgrade!

105°C Long Life

- MVL** 105°C 3,000/5,000H Long Life
- MLE** 105°C 7,000/8,000H Long Life
- MLF** 105°C 10,000H Long Life
- MVJ** 105°C 2,000H
- MLK** 105°C 5,000H Low Profile

Automotive Application

