



ELECTRONIC EQUIPMENT FILM CAPACITOR

HACB Series



- Maximum operating temperature 105°C.
- Allowable temperature rise 15K max.
- A little hum is produced when applied AC voltage.

◆SPECIFICATIONS

Items	Characteristics							
Category temperature range	-40 to +105°C							
Rated voltage range	630 to 4000V _{dc}							
Capacitance tolerance	J: ±5%							
Voltage proof (Terminal - Terminal)	No degradation, at 150% of rated voltage shall be applied for 60 seconds.							
Dissipation factor (tanδ)	No more than 0.05% : Equal or less than 1μF. No more than (c×0.015+0.05)% : More than 1μF.							
Insulation resistance (Terminal - Terminal)	No less than 30000MΩ : Equal or less than 0.33μF.							
	No less than 10000ΩF : More than 0.33μF.							
	Rated voltage (V _{dc})	630	1000	1250	1600	2000	3150	4000
	Measurement voltage (V _{dc})	500	1000	1000	1000	1000	1000	1000
Endurance	The following specifications shall be satisfied, after 1000hrs with applying rated voltage x 125% at 105°C.							
	Appearance	No serious degradation						
	Insulation resistance (Terminal - Terminal)	No less than 10000MΩ : Equal or less than 0.33μF.						
		No less than 3000ΩF : More than 0.33μF.						
	Dissipation factor (tanδ)	Not more than initial specification at 1kHz.						
Loading under damp heat	The following specifications shall be satisfied, after 500hrs with applying rated voltage at 40°C 90~95%RH.							
	Appearance	No serious degradation.						
	Insulation resistance (Terminal - Terminal)	No less than 10000MΩ : Equal or less than 0.33μF.						
		No less than 3000ΩF : More than 0.33μF.						
	Dissipation factor (tanδ)	Not more than initial specification at 1kHz.						
	Capacitance change	Within ±5% of initial value.						

◆STANDARD RATINGS

WV (V _{dc})	Cap (μF)	Dimensions (mm)					Maximum ripple current (Arms)	WV (Vac)	Part Number	Previous part Number (Just for your reference)
		W	H	T	F	φd				
630	0.033	17.7	8.7	8.3	12.5	0.8	3.50	300	FHACB631V333J0LGZ0	HACB2J333J
	0.039		9.3	8.8			3.81		FHACB631V393J0LGZ0	HACB2J393J
	0.047		9.8	9.3			4.18		FHACB631V473J0LGZ0	HACB2J473J
	0.056		10.4	10.0			4.56		FHACB631V563J0LGZ0	HACB2J563J
	0.068		11.3	10.8			5.03		FHACB631V683J0LGZ0	HACB2J683J
	0.082		12.1	11.6			5.52		FHACB631V823J0LGZ0	HACB2J823J
	0.1		13.1	12.5			6.10		FHACB631V104J0LGZ0	HACB2J104J
	0.12		14.0	13.4			6.68		FHACB631V124J0LGZ0	HACB2J124J
	0.15		12.9	12.3			5.67		FHACB631V154J1LHZ0	HACB2J154J
	0.18		13.8	13.2			6.21		FHACB631V184J1LHZ0	HACB2J184J
	0.22	15.1	14.4	6.87	FHACB631V224J1LHZ0	HACB2J224J				
	0.27	16.5	15.7	7.61	FHACB631V274J1LHZ0	HACB2J274J				
	0.33	18.0	17.1	8.41	FHACB631V334J1LHZ0	HACB2J334J				
	0.39	19.3	18.4	9.15	FHACB631V394J1LHZ0	HACB2J394J				
	0.47	18.4	17.5	8.24	FHACB631V474J2LEZ0	HACB2J474J				
	0.56	19.9	18.9	9.00	FHACB631V564J2LEZ0	HACB2J564J				
	0.68	21.7	20.6	9.34	FHACB631V684J2LEZ0	HACB2J684J				
	0.82	23.6	22.5	10.0	FHACB631V824J2LEZ0	HACB2J824J				
	1.0	25.8	24.6	10.0	FHACB631V105J2LEZ0	HACB2J105J				
	1.2	28.1	26.8	10.0	FHACB631V125J2LEZ0	HACB2J125J				
1000	0.018	17.7	8.6	8.3	12.5	0.8	3.00	350	FHACB102V183J0LGZ0	HACB3A183J
	0.022		9.3	8.8			3.32		FHACB102V223J0LGZ0	HACB3A223J
	0.027		9.8	9.5			3.68		FHACB102V273J0LGZ0	HACB3A273J
	0.033		10.7	10.2			4.06		FHACB102V333J0LGZ0	HACB3A333J
	0.039		11.3	10.8			4.42		FHACB102V393J0LGZ0	HACB3A393J
	0.047		12.1	11.6			4.85		FHACB102V473J0LGZ0	HACB3A473J
	0.056		13.0	12.4			5.29		FHACB102V563J0LGZ0	HACB3A563J
	0.068		14.0	13.4			5.83		FHACB102V683J0LGZ0	HACB3A683J
	0.082		12.5	11.9			4.78		FHACB102V823J1LHZ0	HACB3A823J
	0.1		13.5	12.9			5.28		FHACB102V104J1LHZ0	HACB3A104J
	0.12	14.6	13.9	5.79	FHACB102V124J1LHZ0	HACB3A124J				
	0.15	16.1	15.3	6.47	FHACB102V154J1LHZ0	HACB3A154J				
	0.18	17.3	16.5	7.09	FHACB102V184J1LHZ0	HACB3A184J				
	0.22	18.9	18.0	7.83	FHACB102V224J1LHZ0	HACB3A224J				

- (1)Capacitance tolerance:Standard (J:±5%),Option (H:±3%)
- (2)The maximum ripple current : +85°C max., 100kHz, sine wave
- (3)WV(Vac) : 50Hz or 60Hz, sine wave

All products featured in this catalog, which were manufactured by NIPPON CHEMI-CON CORPORATION, are now manufactured by TAITSU CORPORATION, and have been since April 2024.



ELECTRONIC EQUIPMENT FILM CAPACITOR

HACBSeries

◆STANDARD RATINGS

WV (Vdc)	Cap (μF)	Dimensions (mm)					Maximum ripple current (Arms)	WV (Vac)	Part Number	Previous Part Number (Just for your reference)		
		W	H	T	F	φd						
1000	0.27	27.7	18.0	17.1	22.5	1.0	7.07	350	FHACB102V274 J2LEZO	HACB3A274J		
	0.33		19.6	18.6			7.82		FHACB102V334 J2LEZO	HACB3A334J		
	0.39		21.1	20.1			8.50		FHACB102V394 J2LEZO	HACB3A394J		
	0.47		22.9	21.9			9.34		FHACB102V474 J2LEZO	HACB3A474J		
	0.56		25.0	23.8			10.0		FHACB102V564 J2LEZO	HACB3A564J		
	0.68		27.3	26.0			10.0		FHACB102V684 J2LEZO	HACB3A684J		
	0.82	42.7	22.8	21.8	37.5		8.44		FHACB102V824 J4LJZO	HACB3A824J		
	1.0		25.0	23.8			9.34		FHACB102V105 J4LJZO	HACB3A105J		
	1.2		27.1	25.8			10.0		FHACB102V125 J4LJZO	HACB3A125J		
1250	0.012	17.7	8.5	8.2	12.5	0.8	2.68	400	FHACB1C2V123J0LGZO	HACB3B123J		
	0.015		9.2	8.8			3.00		FHACB1C2V153J0LGZO	HACB3B153J		
	0.018		9.8	9.3			3.29		FHACB1C2V183J0LGZO	HACB3B183J		
	0.022		10.5	10.1			3.63		FHACB1C2V223J0LGZO	HACB3B223J		
	0.027		11.3	10.8			4.03		FHACB1C2V273J0LGZO	HACB3B273J		
	0.033		12.2	11.7			4.45		FHACB1C2V333J0LGZO	HACB3B333J		
	0.039	13.1	12.5	4.84	FHACB1C2V393J0LGZO		HACB3B393J					
	0.047	14.0	13.4	5.31	FHACB1C2V473J0LGZO		HACB3B473J					
	0.056	22.7	13.3	12.7	17.5		4.61		FHACB1C2V563J1LHZO	HACB3B563J		
	0.068		14.4	13.7			5.08		FHACB1C2V683J1LHZO	HACB3B683J		
	0.082		15.5	14.8			5.58		FHACB1C2V823J1LHZO	HACB3B823J		
	0.1	27.7	16.9	16.1	22.5		6.16		FHACB1C2V104J1LHZO	HACB3B104J		
	0.12		18.4	17.5			6.75		FHACB1C2V124J1LHZO	HACB3B124J		
	0.15		17.2	16.4			6.02		FHACB1C2V154J2LEZO	HACB3B154J		
	0.18		18.6	17.7			6.60		FHACB1C2V184J2LEZO	HACB3B184J		
	0.22		20.3	19.3			7.29		FHACB1C2V224J2LEZO	HACB3B224J		
	0.27		22.3	21.3			8.08		FHACB1C2V274J2LEZO	HACB3B274J		
	0.33		24.4	23.3			8.93		FHACB1C2V334J2LEZO	HACB3B334J		
	0.39		26.3	25.1			9.34		FHACB1C2V394J2LEZO	HACB3B394J		
	0.47		21.9	20.8			7.10		FHACB1C2V474J4LJZO	HACB3B474J		
	0.56		42.7	23.7			22.6		37.5	7.75	FHACB1C2V564J4LJZO	HACB3B564J
	0.68			25.8			24.6			8.54	FHACB1C2V684J4LJZO	HACB3B684J
	0.82			27.6			26.3			9.34	FHACB1C2V824J4LJZO	HACB3B824J
	1.0	52.7	27.0	25.7	47.5		8.57		FHACB1C2V105JULWZO	HACB3B105J		
1600	0.0047	19.7	8.8	8.5	15.0	0.8	1.32	450	FHACB162V472 JKLDZO	HACB3C472J		
	0.0056		9.3	9.0			1.58		FHACB162V562 JKLDZO	HACB3C562J		
	0.0068		10.0	9.6			1.93		FHACB162V682 JKLDZO	HACB3C682J		
	0.0082		10.7	10.2			2.32		FHACB162V822 JKLDZO	HACB3C822J		
	0.01		11.5	11.0			2.83		FHACB162V103 JKLDZO	HACB3C103J		
	0.012		12.3	11.8			3.39		FHACB162V123 JKLDZO	HACB3C123J		
	0.015	13.5	12.9	4.24	FHACB162V153 JKLDZO		HACB3C153J					
	0.018	14.6	13.9	4.47	FHACB162V183 JKLDZO		HACB3C183J					
	0.022	15.8	15.1	4.94	FHACB162V223 JKLDZO		HACB3C223J					
	0.027	22.7	13.0	12.4	17.5		3.86		FHACB162V273 J1LHZO	HACB3C273J		
	0.033		14.0	13.4			4.27		FHACB162V333 J1LHZO	HACB3C333J		
	0.039		15.1	14.4			4.64		FHACB162V393 J1LHZO	HACB3C393J		
	0.047	27.7	16.4	15.6	22.5		5.09		FHACB162V473 J1LHZO	HACB3C473J		
	0.056		17.6	16.8			5.56		FHACB162V563 J1LHZO	HACB3C563J		
	0.068		19.1	18.2			6.12		FHACB162V683 J1LHZO	HACB3C683J		
	0.082		17.4	16.6			5.29		FHACB162V823 J2LEZO	HACB3C823J		
	0.1		19.0	18.1			5.84		FHACB162V104 J2LEZO	HACB3C104J		
	0.12		20.6	19.6			6.40		FHACB162V124 J2LEZO	HACB3C124J		
	0.15	22.8	21.8	7.15	FHACB162V154 J2LEZO		HACB3C154J					
	0.18	24.7	23.6	7.84	FHACB162V184 J2LEZO		HACB3C184J					
	0.22	27.2	25.9	8.66	FHACB162V224 J2LEZO		HACB3C224J					
	0.27	42.7	23.4	22.3	37.5		6.47		FHACB162V274 J4LJZO	HACB3C274J		
	0.33		25.9	24.7			7.15		FHACB162V334 J4LJZO	HACB3C334J		
	0.39		27.9	26.6			7.77		FHACB162V394 J4LJZO	HACB3C394J		

- (1) Capacitance tolerance:Standard(J:±5%) ,Option(H:±3%)
- (2)The maximum ripple current : +85°C max., 100kHz, sine wave
- (3)WV(Vac) : 50Hz or 60Hz, sine wave

All products featured in this catalog, which were manufactured by NIPPON CHEMI-CON CORPORATION, are now manufactured by TAITSU CORPORATION, and have been since April 2024.